



60 Hz



WUXI LEES POWER COMPANY LIMITED

Add: No.312 National highway,Huishan District,Wuxi,China,214000

Tel: 0086-510-85168446

Email: lees@leespower.com



**“
POWER
GENERATION**

www.leespower.com

LEES Cummins series gensets have a wide power range from 28-4125kVA, which have open type, silent type, trailer type and container type.

All engines comply with standards of ISO 3046, ISO 4001, ISO 8525, IEC 34-1, GB1105, GB/T 2820, CSH 22-2, VDE 0530 and YD/T 502-2000 and so on



60HZ | Three phase

MODEL	POWER				ENGINE	ALTERNATOR			Open Type	Soundproof Type
	Standby KVA	Prime KVA	Standby KW	Prime KW	CUMMINS	STAMFORD	LEROY-SOMER	LEES	Dimension (LxWxH) (mm)	Dimension (LxWxH) (mm)
LSC28S3-6	28	25	22	20	4B3.9-G11	S0L2-M1	TAL A40 G	LA184ES	1900*940*1450	2452X960X1450
LSC35S3-6	35	32	28	25	4B3.9-G2	S0L2-P1	TAL A42 C	LA184F	1900*940*1450	2452X960X1450
LSC38S3-6	38	35	30	28	4B3.9-G12	S1L2-J1	TAL A42 E	LA184G	1900*940*1450	2452X960X1450
LSC50S3-6	50	45	40	36	4BT3.9-G2	S1L2-K1	TAL A42 F	LA184H	1900*940*1450	2452X960X1450
LSC75S3-6	75	68	60	54	4BTA3.9-G2	S1L2-Y1	TAL A42 H	LA224E	1900*940*1450	2452X960X1450
LSC85S3-6	85	78	68	62	4BTA3.9-G2	UCI224F	TAL A44 C	LA224F	1900*940*1450	2452X960X1450
LSC100S3-6	100	90	80	72	4BTA3.9-G11	UCI224F	TAL A44 C	LA224F	1900*940*1450	2452X960X1450
LSC125S3-6	125	113	100	90	6BT5.9-G2	UCI274C	TAL A44 E	LA274C	2250*990*1450	2960*1100*1650
LSC138S3-6	138	125	110	100	6BT5.9-G2	UCI274D	TAL A44 E	LA274D	2250*990*1450	2960*1100*1650
LSC145S3-6	145	130	116	104	6BTA5.9-G2	UCI274D	TAL A44 E	LA274D	2250*990*1450	3360*1110*1700
LSC165S3-6	165	150	132	120	6BTA5.9-G2	UCI274E	TAL A44 H	LA274D	2350*990*1450	3360*1110*1700
LSC184S3-6	184	168	147	134	6BTA5.9-G12	UCI274F	TAL A44 K	LA274F	2415*990*1560	3360*1110*1700
LSC220S3-6	220	200	176	160	6CTA8.3-G2	UCI274G	TAL 044 L	LA274G	2490*1114*1560	3360*1110*1700
LSC250S3-6	250	230	200	184	6CTAA8.3-G2	UCI274H	TAL 044 M	LA274G	2490*1114*1650	3620*1232*2000
LSC275S3-6	275	NA	220	NA	6CTAA8.3-G9	UCI274G	TAL A44 M	LA274G	2490*1114*1650	3620X1232X2050
LSC300S3-6	300	273	240	218	6LTA8.9-G2	UCDI274J	TAL A46 D	LA274J	2680*1150*1700	3620*1232*2000
LSC315S3-6	315	283	252	226	6LTA8.9-G3	UCDI274K	TAL A46 E	LA274K	2780*1150*1700	3910*1332*2100
LSC330S3-6	330	300	264	240	6LTA8.9-G3	UCDI274K	TAL A46 E	LA274K	3200*1150*1800	3910*1332*2100
LSC350S3-6	350	315	280	252	6LTA8.9-G1	S4L1D-D41	TAL A46 F	LA4D	3200*1150*1800	3910*1332*2100
LSC350S3-6-1	350	312	280	250	NTA855-G1	S4L1D-D41	TAL A46 F	LA4D	3370*1250*1950	4260*1462*2100
LSC385S3-6	385	350	308	280	NTA855-G1B	S4L1D-D41	TAL A46 G	LA4D	3370*1250*1950	4260*1462*2100
LSC440S3-6	440	400	352	320	NTA855-G3	S4LID-E41	TAL A473 A	LA4FS	3370*1250*1950	4260*1462*2100
LSC475S3-6	475	430	380	344	6ZTAA13-G2	S4L1D-F41	TAL A473 A	LA4FS	3250*1380*2250	4700*1630*2400
LSC500S3-6	500	475	400	380	QSZ13-G3	S4L1D-F41	TAL A473 A	LA4F	3160*1380*2250	4700*1630*2400
LSC525S3-6	525	475	420	380	QSZ13-G5	S4L1D-F41	TAL A473 A	LA4F	3160*1380*2250	4700*1630*2400
LSC575S3-6	575	523	460	418	KTA19-G3	S4L1D-G41	TAL A473 B	LA5C	3600*1400*2150	4700*1630*2400
LSC600S3-6	600	550	480	440	QSZ13-G11	HCI544D/S5L1D-D4	TAL A473 C	LA5C	3600*1400*2150	4700X1630X2400
LSC635S3-6	635	580	508	464	KTA19-G3A	HCI544D/S5L1D-D4	TAL A473 C	LA5D	3600*1400*2150	4700*1630*2400
LSC688S3-6-1	688	588	550	470	KTA19-G5	HCI544E/S5L1D-E4	TAL A473 E	LA5ES	3600*1400*2150	4700*1630*2400
LSC688S3-6	688	625	550	500	QSK19-G4	HCI544E/S5L1D-E4	TAL A473 E	LA5ES	3650*1638*2050	5060*1912*2500
LSC750S3-6	750	NA	600	NA	KTA19-G6A	HCI544E/S5L1D-E4	TAL A473 E	LA5E	3950x1638x2150	5060*1912*2530
LSC750S3-6-E	750	688	600	550	QSK19-G5	HCI544F/S5L1D-F4	TAL A473 F	LA5E	3950x1638x2150	5060*1912*2500
LSC850S3-6	850	765	680	612	KTA38-G	HCI544F/S5L1D-F4	TAL A49B	LA5FS	4350x2100x2320	5400*2260*2550/20HQ
LSC950S3-6	950	855	760	684	KTA38-G1	S6L1D-C4	TAL A49 C	LA6B	4350x2100x2320	5400*2260*2550/20HQ
LSC1000S3-6	1000	910	800	728	KTA38-G2	S6L1D-C4	TAL A49 C	LA6C	4550x2100x2320	5400*2260*2550/20HQ
LSC1130S3-6	1130	1030	904	824	KTA38-G2A	S6L1D-D4	TAL A49 D	LA6D	4750x2100x2320	5400*2260*2550/20HQ
LSC1265S3-6	1250	1125	1000	900	KTA38-G4	S6L1D-E4	TAL A49 E	LA6E	4750x2100x2320	5806*2260*2554/20HQ
LSC1375S3-6	1375	NA	1100	NA	KTA38-G9	S6L1D-F4	LSA 50.2 M6	LA6E	4750x2100x2320	5400*2260*2550

60HZ | Three phase

MODEL	POWER				ENGINE	ALTERNATOR			Open Type	Soundproof Type
	Standby KVA	Prime KVA	Standby KW	Prime KW	CUMMINS	STAMFORD	LEROY-SOMER	LEES	Dimension (LxWxH) (mm)	Dimension (LxWxH) (mm)
LSC1600S3-6	1600	1410	1280	1128	KTA50-G3	S6L1D-H4	LSA 50.2 M6	LA6G	5283*2260x2510	ISO 20/40ft GP
LSC1930S3-6	1930	1610	1544	1288	KTA50-G9	S7L1D-C4	LSA 50.2 VL10	LA7F	5820x2200x2800	ISO 20ft HQ
LSIC1000S3-6	1000	910	800	728	QSK23-G3	S6L1D-C4	TAL A49 C	LA6C	4600x1650x2090	ISO 20ft GP
LSIC1265S3-6	1265	1150	1012	920	QST30-G4	S6L1D-E4	TAL A49 E	LA6E	4750x1650x2250	ISO 20ft HQ
LSIC1565S3-6	1565	1420	1252	1136	QSK50-G2	S6L1D-G4	LSA 50.2 M6	LA6G	5283*2260x2510	ISO 20ft HQ
LSIC1875S3-6	1875	1700	1500	1360	QSK50-G4/G11	S7L1D-C4	LSA 50.2 VL10	LA7F	5820x2200x2510	ISO 20ft HQ
LSIC2000S3-6	2000	1820	1600	1456	QSK50-G6	S7L1D-D4	LSA 50.2 VL10	LA7F	5820x2200x2510	ISO 20ft HQ
LSIC2500S3-6	2500	2281	2000	1825	QSK60-G6/G7	S7L1D-F4	LSA 52.3 S7	LA7FS	6250*2500*2510	ISO 40ft HQ
LSIC2813S3-6	2750	NA	2200	NA	QSK60-G9	S7L1D-J4	LSA 52.3 L9	/	6250*2500*2510	ISO 40ft HQ
LSIC3125S3-6	3125	NA	2500	NA	QSK60-G19	P80 LVSI804S	LSA 52.3 L12	/	6250*2500*2510	ISO 40ft HQ
LSIC3125S3-6-1	3125	2844	2500	2275	QSK78-G6/G7	P80 LVSI804S	/	/	7350*2700*3410	ISO 40ft HQ
LSIC3438S3-6	3438	3125	2750	2500	QSK78-G8/G19	P80 LVSI804T	/	/	7350*2700*3410	ISO 40ft HQ
LSIC3750S3-6	3750	NA	3000	NA	QSK95-G11	P80 LVSI804W	/	/	7800*3100*3410	ISO 40ft HQ
LSIC4125S3-6	4125	3750	3300	3000	QSK95-G2	P80 LVSI804X	/	/	7800*3100*3410	ISO 40ft HQ



LEES Perkins series gensets have a wide power range from 13-1880KVA, which have open type, silent type, trailer type and container type.

As the world's leading engine manufacturer, Perkins is the leader of this industry from 8-2000KW because of its economy, reliability and durability.

60HZ | Three phase

MODEL	POWER				ENGINE	ALTERNATOR			Open Type	Soundproof Type
	Standby KVA	Prime KVA	Standby KW	Prime KW	PERKINS	STAMFORD	LEREOY-SOMER	LEES	Dimension (LxWxH) (mm)	Dimension (LxWxH) (mm)
LSP13S3-6	13	12	10	9	403D-11G	PI044E	TAL A40 C	LA164B	1300x690x1000	1860X810X1152
LSP17S3-6	17	16	14	13	403D-15G	SOL1-P1	TAL A40 E	LA164C	1400x690x1000	1860X810X1152
LSP20S3-6	20	18	16	14	403A-15G2	SOL2-F1	TAL A40 E	LA164D	1300x690x1000	1860X810X1152
LSP26S3-6	26	24	21	19	404D-22G	PI144D	TAL A40 G	LA184ES	1470x690x1280	1860X810X1152
LSP35S3-6	36	33	29	26	404D-22TG	SOL2-P1	TAL A42 C	LA184F	1470*790*1280	1860X810X1152
LSP40S3-6	38	35	30	28	1103A-33G	S1L2-J1	TAL A42 E	LA184G	1600x790x1320	2152X960X1450
LSP59S3-6	59	53	47	42	1103A-33TG1	S1L2-R1	TAL A42 G	LA224D	1600x790x1280	2152X960X1450
LSP70S3-6	71	NA	57	NA	1104D-44TG1	S1L2-Y1	TAL A42 H	LA224E	2000x850x1350	2510*1060*1600
LSP75S3-6	75	68	60	54	1103A-33TG2	S1L2-Y1	TAL A42 H	LA224E	1600x790x1280	2152X960X1450
LSP84S3-6	84	76	67	61	1104A-44TG1	UCI224F	TAL A44 E	LA224F	2000x850x1350	2510*1060*1600
LSP100S3-6	100	90	80	72	1104A-44TG2	UCI224G	TAL A44 D	LA224G	2000x850x1350	2510*1060*1600
LSP125S3-6	125	112	100	90	1104C-44TAG2	UCI274C	TAL A44 E	LA274C	2250x960x1350	2960*1100*1650
LSP170S3-6	169	152	135	122	1106A-70TAG1	UCI274E	TAL A44J	LA274ES	2650x960x1650	3360*1110*1750
LSP190S3-6	190	169	150	135	1106A-70TAG2	UCI274F	TAL A44 K	LA274F	2650x960x1650	3360*1110*1750
LSP220S3-6	220	200	176	160	1106A-70TAG3	UCI274G	TAL A44 L	LA274G	2650x960x1650	3360*1110*1750
LSP250S3-6	250	225	200	180	1206A-E70TTAG1	UCI274H	TAL A46 C	LA274H	2780x1200x1770	3620X1232X2050
LSP395S3-6	395	357	316	286	1706A-E93TAG1	S4L1D-D4	TAL A46G	LA4D	3100x1260x1770	3910*1332*2050
LSP440S3-6	440	400	352	320	2206C-E13TAG2	S4L1D-E41	TAL A46H	LA4FS	3490x1330x2050	4260*1462*2100
LSP500S3-6	500	438	400	350	2206A-E13TAG6	S4L1D-F41	TAL A473 A	LA4F	3490x1330x2050	4260*1462*2100
LSP565S3-6	550	500	440	400	2506C-E15TAG1	S4L1D-F41	TAL A473 A	LA4G	3750x1350x2100	4700*1630*2430
LSP625S3-6	625	575	500	460	2506C-E15TAG3	HCI544D/S5L1D-D4	TAL A473 C	LA5D	3750x1350x2100	4700*1630*2430
LSP700S3-6	687	NA	550	NA	2806C-E18TAG1A	HCI544E/S5L1D-E4	TAL A473 E	LA5ES	3600x1750x2200	5060*1912*2500
LSP750S3-6	750	NA	600	NA	2806C-E18TAG3	HCI544E/S5L1D-E4	TAL A473 E	LA5E	3600x1750x2200	5060*1912*2500
LSP825S3-6	825	750	660	600	4006-23TAG2A	HCI544F/S5L1D-F4	TAL A473 F	LA5F	4350*1750*2270	5400*2260*2550
LSP945S3-6	945	850	755	680	4006-23TAG3A	S6L1D-C4	TAL A49 C	LA6B	4350*1750*2270	5400*2260*2550
LSP975S3-6	975	884	780	707	4008TAG1A	S6L1D-C4	TAL A49 C	LA6C	4750*2070*2414	5400*2260*2550
LSP1100S3-6	1100	1000	880	800	4008TAG2	S6L1D-D4	TAL A49 D	LA6D	4750*2070*2414	5400*2260*2550
LSP1375S3-6	1375	1250	1100	1000	4012-46TWG2A	S6L1D-F4	LSA 50.2 M6	LA6F	5000x2182x2460	ISO40'ft GP
LSP1500S3-6	1500	1375	1200	1100	4012-46TWG3A	S6L1D-G4	LSA 50.2 M6	LA6G	5000x2182x2460	ISO 40'ft HQ
LSP1675S3-6	1675	1500	1340	1200	4012-46TAG2A	S6L1D-H4	LSA 50.2 L7	LA7B	5000*2182*2436	ISO 40'ft HQ
LSP1880S3-6	1880	1700	1504	1360	4012-46TAG3A	S7L1D-C4	LSA 50.2 L8	LA7G	5200*2200*2477	ISO 40'ft HQ

*Powered by PERKINS, three phase, 127/220V, 254/440V, 1800RPM, 60HZ
Voltage available: 240/416V, 254/440V, 277/480V, 120/208V, 127/220V
Please contact us at lees@leespower.com, for more product specifications.

LEES MTU series gensets are with the power range of 900-4000KVA.

MTU engine has always been well known for its large output power, high efficiency, small size and durability.

It is one of the most advanced engine manufacturers in the world.

60HZ | Three phase

MODEL	POWER				ENGINE	ALTERNATOR			Open Type	Soundproof Type
	Standby KVA	Prime KVA	Standby KW	Prime KW	MTU	STAMFORD	LEREOY-SOMER	LEES	Dimension (LxWxH) (mm)	Dimension (LxWxH) (mm)
LSM900S3-6	900	815	717	652	12V2000G45	S6L1D-C4	LSA 49.3 M6	/	3965x1710x2200	5800x1800x2550
LSM1020S3-6	1020	930	816	744	12V2000G85	S6L1D-C4	LSA 49.3 M8	/	4700x1780x2400	5806*2260*2554
LSM1160S3-6	1160	1000	928	800	16V2000G45	S6L1D-D4	LSA 49.3 L9	/	5000x2200x2850	5806*2260*2554
LSM1280S3-6	1280	1160	1024	928	16V2000G85	S6L1D-E4	LSA 49.3 L10	/	5000x2200x2850	5806*2260*2554
LSM1510S3-6	1510	1370	1208	1096	18V2000G85	S6L1D-F4	LSA 50.2 M6	/	5100x2200x2850	ISO 20'ft GP
LSM1965S3-6	1965	1730	1572	1384	12V4000G43S	S7L1D-C4	LSA 50.2 L8	/	5400x2650x2650	ISO 20'ft HQ
LSM2175S3-6	2175	1975	1740	1580	12V4000G83S	S7L1D-E4	LSA 52.3 S5	/	6000x2700x3400	ISO 40'ft HQ
LSM2615S3-6	2615	2315	2092	1852	16V4000G43S	S7L1D-F4	LSA 52.3 S7	/	6000x2700x3400	ISO 40'ft HQ
LSM2865S3-6	2865	2600	2292	2080	16V4000G83S	S7L1D-J4	LSA 52.3 L9	/	6000x2700x3400	ISO 40'ft HQ
LSM3140S3-6	3140	2850	2512	2280	20V4000G43S	LVSI 804S	LSA 52.3 L12	/	6000x2700x3400	ISO 40'ft HQ
LSM3450S3-6	3450	3140	2760	2512	20V4000G83S	LVSI 804T	LSA 52.3 UL16	/	6000x2700x3400	ISO 40'ft HQ
LSM4000S3-6	4000	3465	3200	2772	20V4000G83LS	LVSI 804W	LSA 53.2 M12	/	6000x2700x3400	ISO 40'ft HQ

*Powered by MTU, three phase, 127/220V, 254/440V, 1800RPM, 60HZ
Voltage available: 240/416V, 254/440V, 277/480V, 120/208V, 127/220V
Please contact us at lees@leespower.com, for more product specifications.





LEES Hyundai series gensets are with the power range of 55-1125kVA.

Hyundai diesel engine is small in size, light in weight, strong in anti-sudden load capacity, low in noise, reliable in economy and enjoys a good reputation all over the world.

60HZ | Three phase

MODEL	POWER				ENGINE	ALTERNATOR			Open Type	Soundproof Type
	Standby KVA	Prime KVA	Standby KW	Prime KW	HYUNDAI	LEROY-SOMER	LEES	STAMFORD	Dimension (LxWxH) (mm)	Dimension (LxWxH) (mm)
LSDS55S3-6	63	58	50	46	SP344CA	TAL-A42-H	LA 224D	S1L2-Y1	/	/
LSDS70S3-6	80	73	64	58	SP344CB	TAL-A42-H	LA 224E	S1L2-Y1	/	/
LSDS88S3-6	100	91	80	73	SP344CC	TAL A44 C	LA224F	UCI224G	/	/
LSDS200S3-6	201	180	161	144	DP086TA	TAL A44 K	LA274F	UCI274F	2620*1150*1700	3620*1232*2050
LSDS213S3-6	213	193	170	154	P086TI-1	TAL A44 L	LA274F	UCI274G	2680*1150*1700	3620*1232*2050
LSDS250S3-6	250	225	200	180	P086TI	TAL A44 M	LA274G	UCI274H	2720*1150*1700	3620*1232*2050
LSDS285S3-6	285	255	228	204	DP086LA	TAL A46 C	LA274J	UCDI274J	2780*1150*1700	3620*1232*2050
LSDS350S3-6	350	310	280	248	P126TI	TAL A46 E	LA4D	S4L1D-D41	3100*1230*1700	4260*1462*2100
LSDS385S3-6	385	344	308	275	P126TI-II	TAL A46 G	LA4D	S4L1D-D41	3100*1230*1700	4260*1462*2100
LSDS440S3-6	440	402	352	321	DP126LB	TAL A46 H	LA4FS	S4LID-E41	3100*1230*1700	4260*1462*2100
LSDS510S3-6	510	444	408	355	P158LE	TAL A473 A	LA4FG	S4L1D-F41	3000*1340*2000	4260*1612*2300
LSDS575S3-6	575	521	460	416	DP158LC	TAL A473 B	LA5C	S4L1D-G41	3000*1340*2000	4260*1612*2300
LSDS650S3-6	650	590	520	472	DP158LD	TAL A473 D	LA5D	S5L1D-D4	3000*1340*2000	4260*1612*2300
LSDS700S3-6	700	630	560	504	DP180LA	TAL A473 E	LA5ES	S5L1D-E4	3200*1400*2050	4700*1630*2430
LSDS750S3-6	750	679	600	543	DP180LB	TAL A473 E	LA5E	S5L1D-E4	3200*1400*2050	4700*1630*2430
LSDS825S3-6	825	750	660	600	DP222LA	TAL A473 F	LA5E	S5L1D-F4	3700*1450*2300	5060*1700*2500
LSDS880S3-6	880	800	704	640	DP222LB	TAL A49 B	LA5F	S6L1D-C41	3700*1450*2300	5060*1700*2500
LSDS935S3-6	935	850	749	680	DP222LC	TAL A49 C	LA6B	S6L1D-C41	3700*1450*2300	5060*1700*2500
LSDS950S3-6	950	865	760	692	DP222CA	TAL A49 C	LA6C	S6L1D-C41	3960*1900*2250	5060*1912*2530
LSDS1025S3-6	1025	940	820	752	DP222CB	TAL A49 D	LA6C	S61D-D4	3960*1900*2250	5060*1912*2530
LSDS1125S3-6	1125	1000	900	800	DP222CC	TAL A49 D	LA6D	S61D-D4	3960*1900*2250	5060*1912*2530

*Powered by Hyundai, three phase, 127/220V, 254/440V, 1800RPM, 60HZ
Voltage available: 240/416V, 254/440V, 277/480V, 120/208V, 127/220V
Please contact us at lees@leespower.com, for more product specifications.



LEES Volvo series gensets are with the power range of 94-800kVA.

Volvo engines have good emissions like Tier2 and Tier3 to meet the requirements of environmental protection. Also with low fuel consumption, low noise and stable performance under continuous use.

60HZ | Three phase

MODEL	POWER				ENGINE	ALTERNATOR				Open Type	Soundproof Type
	Standby KVA	Prime KVA	Standby KW	Prime KW	VOLVO	STAMFORD	LEROY-SOMER	LEES	Dimension (LxWxH) (mm)	Dimension (LxWxH) (mm)	
60HZ 220/440V 3P4W Tier2											
LSV94S3-6	94	85	75	68	TAD530GE	UCI224G	TAL A44 C	/	1850x900x1560	2910*1100*1650	
LSV110S3-6	110	100	88	80	TAD531GE	UCI274C	TAL A44 D	/	2150x900x1560	2910*1100*1650	
LSV142S3-6	142	130	114	104	TAD532GE	UCI274D	TAL A44 H	/	2150x900x1560	2910*1100*1650	
LSV165S3-6	165	150	132	120	TAD731GE	UCI274E	TAL A44 J	/	2415x930x1655	3360*1110*1700	
LSV220S3-6	220	200	176	160	TAD732GE	UCI274G	TAL A44 L	/	2580x930x1670	3620*1232*2000	
LSV250S3-6	250	221	200	177	TAD733GE	UCI274H	TAL A44 M	/	2580x930x1670	3620*1232*2000	
LSV285S3-6	285	250	228	200	TAD734GE	UCDI274J	TAL A46 C	/	2580x930x1670	3620*1232*2000	
LSV278S3-6	278	253	222	202	TAD841GE	UCDI274J	TAL A46 D	/	2760x1050x1650	3620*1232*2000	
LSV330S3-6	330	300	264	240	TAD842GE	S4LID-D41	TAL A46 F	/	2760x1050x1650	3620*1232*2000	
LSV350S3-6	350	320	280	256	TAD843GE	S4LID-D41	TAL A46 G	/	3100x1120x1788	3910*1332*2050	
LSV380S3-6	380	345	304	276	TAD1341GE-B	S4L1D-D41	TAL A46 G	/	3100x1120x1788	3910*1332*2050	
LSV440S3-6	440	400	352	320	TAD1342GE-B	S4L1D-E41	TAL A46 H	/	3100x1120x1788	3910*1332*2050	
LSV455S3-6	455	415	364	332	TAD1343GE-B	S4LID-E41	TAL A473 A	/	3400x1270x1974	4260*1450*2100	
LSV500S3-6	500	450	400	360	TAD1344GE-B	S4L1D-F41	TAL A473 A	/	3400x1270x1974	4260*1450*2100	
LSV510S3-6	510	460	408	368	TAD1345GE-B	S4L1D-F41	TAL A473 A	/	3400x1270x1974	4700*1630*2350	
LSV630S3-6	630	575	504	460	TAD1641GE-B	HCI544D/S5L1D-D4	TAL A473 C	/	3400x1270x1974	5060*1912*2530	
LSV700S3-6	700	630	560	504	TAD1642GE-B	HCI544E/S5L1D-E4	TAL A473 E	/	3400x1270x1974	5060*1912*2530	
LSV800S3-6	800	727	640	582	TWD1645GE	HCI544F/S5L1D-F4	TAL A473 F	/	2830x1300x1670	3620X1232X2050	
60HZ 220/440V 3P4W Tier3											
LSV95S3-6E	101	94	81	75	TAD550GE	UCI224G	TAL A44 D	/	1850x900x1560	2910*1100*1650	
LSV110S3-6E	120	112	96	90	TAD551GE	UCI274C	TAL A44 E	/	2150x900x1560	2910*1100*1650	
LSV145S3-6E	160	145	128	116	TAD750GE	UCI274E	TAL A44 J	/	2415x930x1655	3360*1110*1700	
LSV170S3-6E	187	170	150	136	TAD751GE	UCI274F	TAL A44 K	/	2580x930x1670	3620*1232*2000	
LSV200S3-6E	220	200	176	160	TAD752GE	UCI274G	TAL A44 L	/	2580x930x1670	3620*1232*2000	
LSV255S3-6E	255	225	204	180	TAD753GE	UCI274H	TAL A44 M	/	2830x1300x1670	3620X1232X2050	
LSV285S3-6E	285	250	228	200	TAD754GE	UCDI274J	TAL A46 C	/	2900x1300x1670	3910*1332*2050	
LSV315S3-6E	315	283	252	226	TAD1350GE	S4L1D-C41	TAL A46 E	/	3250x1350x1800	4260*1450*2100	
LSV375S3-6E	380	345	304	276	TAD1351GE	S4L1D-D41	TAL A46 G	/	3250x1350x1800	4260*1450*2100	
LSV440S3-6E	440	400	352	320	TAD1352GE	S4L1D-E41	TAL A46 H	/	3250x1350x1800	4260*1450*2100	
LSV500S3-6E	500	450	400	360	TAD1353GE	S4L1D-F41	TAL A473 A	/	3250x1350x1800	4260*1450*2100	
LSV565S3-6E	565	513	452	410	TAD1650GE	HCI544C/S5L1D-C4	TAL A473 B	/	3600x1680x2100	4700*1630*2350	
LSV640S3-6E	640	585	512	468	TAD1651GE	HCI544D/S5L1D-D4	TAL A473 C	/	3600x1680x2100	4700*1630*2350	

*Powered by VOLVO, three phase, 127/220V, 254/440V, 1800RPM, 60HZ
Voltage available: 240/416V, 254/440V, 277/480V, 120/208V, 127/220V
Please contact us at lees@leespower.com, for more product specifications.

60HZ | Single phase

MODEL	POWER				ENGINE	ALTERNATOR	Open Type	Soundproof Type
	Standby KVA	Prime KVA	Standby KW	Prime KW	LEES	LEES	Dimension (LxWxH) (mm)	Dimension (LxWxH) (mm)
LSY10S-6	9.5	8.6	9.5	8.6	YD380D	LA164C	/	1680x800x1050
LSY11S-6	11.4	10.4	11.4	10.4	YD385D	LA164D	/	1680x800x1050
LSY14S-6	14.1	12.8	14.1	12.8	YD480D	LA184E	/	1680x800x1050
LSY18S-6	17.6	16.0	17.6	16.0	YND485D	LA184F	/	1840x800x1050
LSY22S-6	22.0	20.0	22.0	20.0	YND490D	LA184G	/	1840x800x1050
LSY26S-6	26.4	24.0	26.4	24.0	Y495D	LA184H	/	1950x800x1050
LSY31S-6	30.8	28.0	30.8	28.0	Y4100D	LA184J	/	2100x880x1150
LSY39S-6	39.0	31.2	39.0	31.2	Y4105D	LA224C	/	2100x880x1150
LSY46S-6	46.4	41.7	46.4	41.7	Y4102ZLD	LA224E	/	2460x1000x1257
LSY52S-6	52.0	46.8	52.0	46.8	Y4105ZLD	LA224E	/	2460x1000x1257
LSY60S-6	60.0	54.0	60.0	54.0	YD4EZLD	LA224F	/	2460x1000x1257
LSY77S-6	77.0	70.0	77.0	70.0	Y4110ZLD	LA224G	/	2460x1000x1257

*Powered by LEES, single phase 120/240V, three phase 127/220V, 254/440V, 1800RPM, 60HZ

Voltage available: 240/416V, 254/440V, 277/480V, 120/208V, 127/220V

Please contact us at lees@leespower.com, for more product specifications.



60HZ | Three phase

MODEL	POWER				ENGINE	ALTERNATOR	Open Type	Soundproof Type
	Standby KVA	Prime KVA	Standby KW	Prime KW	LEES	LEES	Dimension (LxWxH) (mm)	Dimension (LxWxH) (mm)
LSY13S3-6	13.2	12.0	10.6	9.6	YD380D	LA164B	/	1680x800x1050
LSY14S3-6	14.3	13.0	11.4	10.4	YD385D	LA164B	/	1680x800x1050
LSY18S3-6	17.6	16.0	14.0	12.8	YD480D	LA164C	/	1680x800x1050
LSY21S3-6	20.5	18.6	16.5	15.0	YND485D	LA164D	/	1840x800x1050
LSY28S3-6	27.5	25.0	22.0	20.0	YND490D	LA184ES	/	1840x800x1050
LSY33S3-6	33.0	30.0	26.4	24.0	Y495D	LA184F	/	1950x800x1050
LSY39S3-6	38.5	35.0	30.8	28.0	Y4100D	LA184G	/	2100x880x1150
LSY49S3-6	48.7	44.3	39.0	35.4	Y4105D	LA184H	/	2100x880x1150
LSY58S3-6	57.3	52.1	45.8	41.7	Y4102ZLD	LA224D	/	2460x1000x1257
LSY65S3-6	64.7	58.8	51.7	47.0	Y4105ZLD	LA224D	/	2460x1000x1257
LSY76S3-6	75.5	68.6	60.4	54.9	YD4EZLD	LA224E	/	2460x1000x1257
LSY97S3-6	97.0	88.2	77.6	70.6	Y4110ZLD	LA224F	/	2560x1000x1257
LSSC12S3-6	125	113	100	90	4HTAA4.3-G21	LA274C	2100x950x1200	2960x1100x1650
LSSC140S3-6	140	125	112	100	4HTAA4.3-G23	LA274D	2100x950x1200	2960x1100x1650
LSSC165S3-6	165	150	132	120	6HTAA6.5-G21	LA274ES	2450x980x1380	3360x1110x1700
LSSC180S3-6	180	165	144	132	6HTAA6.5-G22	LA274E	2450x980x1380	3360x1110x1700
LSSC220S3-6	220	200	176	160	6HTAA6.5-G23	LA274G	2450x980x1380	3360x1110x1700
LSSC250S3-6	250	225	200	180	6DTAA8.9-G21	LA274H	2550x980x1500	3620x1232x2050
LSSC275S3-6	275	250	220	200	6DTAA8.9-G24	LA274J	2750x1050x1500	3910x1332x2100
LSSC312S3-6	313	275	250	220	6DTAA8.9-G23	LA274K	3160x1050x1700	4260x1462x2100
LSSC375S3-6	375	350	300	280	6ETAA11.8-G21	LA4D	3160x1050x1700	4260x1462x2100
LSSC400S3-6	400	360	320	288	6ETAA12.8-G22	LA4ES	3260x1050x1500	4260x1462x2100
LSSC440S3-6	440	400	352	320	6ETAA12.8-G21	LA4FS	3260x1050x1500	4260x1462x2100
LSSC500S3-6	500	450	400	360	6ETAA12.8-G32	LA4F	3260x1050x1500	4260x1462x2100
LSSC550S3-6	550	500	440	400	6ETAA12.8-G31	LA4G	3260x1050x1500	4260x1462x2100
LSSC625S3-6	625	563	500	450	6KTAA25-G311	LA5D	3550x1450x2000	4700x1630x2400
LSSC688S3-6	688	625	550	500	6KTAA25-G310	LA5ES	3550x1450x2000	4700x1630x2400
LSSC750S3-6	750	700	600	560	6KTAA25-G39	LA5E	3550x1450x2000	4700x1630x2400
LSSC825S3-6	825	750	660	600	6KTAA25-G32.1	LA5F	3550x1450x2000	4700x1630x2400
LSSC900S3-6	900	825	720	660	6KTAA25-G31.1	LA6B	3550x1450x2000	4700x1630x2400

RENTAL PROJECTS

- Easy for movement and transportation
- Strong structural design and materials
- Compact size
- Switchable from internal and external fuel tank
- Large capacity of double-wall fuel tank
- Large space of outlet
- Applicated for different special cases such as seaside, construction and mining
- Intelligent: GPS monitoring, remote operation etc
- Low noise level





PROJECT CASES



